

## **Negarra Product Index**

### **Page Number**

- 2. Negarra MD Plus 125mm-200mm**
- 3. Negarra MD Plus 250mm-400mm**
- 4. Negarra GC Plus 80mm-150mm**
- 5. Negarra GC Plus 175mm-300mm**
- 6. Negarra GC Plus 350mm-500mm**
- 7. Negarra GC Plus 550mm-650mm**



# Negarra MD Plus

## Twin-Wall Insulated Flue (AISI 316 inner/304 outer)

Multi-Fuel Chimney System for Gas, Oil and Solid Fuel

Description	125mm Diameter		150mm. Diameter		175mm Diameter		200mm. Diameter	
	Code	£	Code	£	Code	£	Code	£
Pipe 100mm.	720,103	59.74	721,103	64.23	722,103	65.99	723,103	67.84
Pipe 250mm.	720,104	60.53	721,104	65.73	722,104	67.84	723,104	69.60
Pipe 500mm.	720,105	63.96	721,105	69.60	722,105	73.13	723,105	82.82
Pipe 1000mm.	720,106	88.99	721,106	100.44	722,106	117.18	723,106	130.40
Adjust Pipe 250-450mm.	720,108	111.01	721,108	122.47	722,108	129.52	723,108	140.09
Adjust Pipe 500-950mm.	720,107	133.92	721,107	148.02	722,107	155.95	723,107	177.97
Inspection Pipe 500mm	720,120	107.49	721,120	123.35	722,120	144.49	723,120	161.23
Inspection Squ Door	720,350	163.88	721,350	176.21	722,350	199.12	723,350	261.67
Damper 250mm.	720,134	121.59	721,134	125.11	722,134	131.28	723,134	134.80
Silencer 1000mm.	720,133	111.89	721,133	128.63	722,133	149.78	723,133	167.40
15° Elbow	720,015	74.89	721,015	77.53	722,015	88.99	723,015	92.51
30° Elbow	720,030	74.89	721,030	77.53	722,030	88.99	723,030	92.51
45° Elbow	720,045	79.30	721,045	81.94	722,045	90.75	723,045	98.68
90° Elbow	720,090	135.68	721,090	140.09	722,090	154.19	723,090	167.40
90° Tee	720,109	146.26	721,109	163.00	722,109	176.21	723,109	200.88
135° Tee	720,110	193.83	721,110	228.19	722,110	245.82	723,110	275.77
Locking Band	118,114	9.25	119,114	9.96	120,114	10.57	121,114	11.89
Structural Locking Band	720,135	28.50	721,135	32.10	722,135	34.83	723,135	38.31
Adjustable Wall Bracket	118,115	18.94	119,115	20.70	120,115	23.00	121,115	24.85
Level Bracket	118,118	37.45	119,118	40.62	120,118	45.11	121,118	50.84
Guy Wire Bracket	118,117	13.04	119,117	13.48	120,117	13.74	121,117	14.63
Descend Bracket	118,181	18.50	119,181	21.23	120,181	22.91	121,181	24.67
Adjustable Wall Support	118,121	63.26	119,121	73.13	120,121	81.94	121,121	91.63
Floor Support	118,124	101.32	119,124	111.89	120,124	121.59	121,124	132.16
Base Support with Drain	720,119	87.22	721,119	96.92	722,119	105.73	723,119	113.66
Roof Support	118,136	33.30	119,136	42.11	120,136	42.82	121,136	43.17
Level Support	118,137	31.01	119,137	32.60	120,137	37.18	121,137	40.00
Conical Terminal	720,111	37.18	721,111	43.44	722,111	46.96	723,111	53.22
Rain Cap	118,112	28.55	119,112	31.81	120,112	39.03	121,112	49.69
Double Rain Cap	118,123	41.67	119,123	47.84	120,123	52.25	121,123	60.26
Anti-Flying Top Terminal	118,127	52.07	119,127	60.26	120,127	63.44	121,127	70.48
Anti-Wind Top Terminal	118,125	57.62	119,125	66.08	120,125	72.25	121,125	79.30
Static Terminal	118,131	54.54	119,131	61.94	120,131	67.84	121,131	74.01
Boiler Adaptor			721,150	26.78 (Ø 125)	120,150	27.49	121,150	30.13
Boiler Adaptor	720,151	25.29 (Ø 125)			722,151	30.22 (Ø 175)	723,151	33.04 (Ø 200)
Boiler Adaptor			721,152	26.78 (Ø 150)				
Boiler Adaptor 100Ø125	118,157	23.00 (Ø 100)						
Single-Double Adaptor	720,148	26.34	721,148	27.84	722,148	31.37	723,148	34.36
Double-Single Adaptor	720,149	26.34	721,149	27.84	722,149	31.37	723,149	34.36
Adaptor GC to MD	527,170	49.87 (Ø 135)	528,170	54.71				
Adaptor MD to GC	527,171	49.87 (Ø 140)	528,171	54.71				
Adaptor GC to MD					529,170	63.79	530,170	77.53
Adaptor MD to GC					529,171	63.79	530,171	77.53
Increaser (*)	720,160	74.89 (Ø 150)	721,160	82.82 (Ø 175)	722,160	103.08 (Ø 200)	723,160	111.01 (Ø 250)
Increaser	720,161	79.30 (Ø 175)	721,161	90.75 (Ø 200)	722,161	111.01 (Ø 250)	723,161	122.47 (Ø 300)
Increaser	720,162	88.11 (Ø 200)	721,162	97.80 (Ø 250)				
Teecap	118,113	20.70	119,113	23.00	120,113	25.73	121,113	29.25
Teecap with Drain	118,145	22.11	119,145	24.85	120,145	26.52	121,145	31.10
Firestop Plate	118,140	14.53	119,140	16.30	120,140	18.59	121,140	22.11
Support Clamp & Plate	118,182	33.65	119,182	36.12	120,182	39.38	121,182	44.23
Base Support Plate	720,183	34.62	721,183	39.56	722,183	44.49	723,183	49.43
0° - 10° Flashing	118,129	50.57	119,129	58.50	120,129	64.76	121,129	69.60
5° - 35° Flashing	118,130	50.57	119,130	58.50	120,130	64.76	121,130	69.60
30° - 45° Flashing	118,147	50.57	119,147	58.50	120,147	64.76	121,147	69.60
Storm Collar	118,132	18.86	119,132	20.35	120,132	20.62	121,132	22.11

(\* ) These sizes made to order



# Negarra MD Plus

## Twin-Wall Insulated Flue (AISI 316 inner/304 outer)

Multi-Fuel Chimney System for Gas, Oil and Solid Fuel

Description	250mm Diameter		300mm. Diameter		350mm Diameter		400mm. Diameter	
	Code	£	Code	£	Code	£	Code	£
Pipe 100mm.	<b>724,103</b>	87.22	<b>725,103</b>	96.04				
Pipe 250mm.	<b>724,104</b>	88.99	<b>725,104</b>	97.80	<b>726,104</b>	125.11	<b>727,104</b>	156.83
Pipe 500mm.	<b>724,105</b>	95.15	<b>725,105</b>	111.89	<b>726,105</b>	156.83	<b>727,105</b>	194.71
Pipe 1000mm.	<b>724,106</b>	162.11	<b>725,106</b>	195.60	<b>726,106</b>	268.72	<b>727,106</b>	322.47
Adjust Pipe 250-450mm.	<b>724,108</b>	162.11	<b>725,108</b>	179.74	<b>726,108</b>	239.65	<b>727,108</b>	307.49
Adjust Pipe 500-950mm.	<b>724,107</b>	195.60	<b>725,107</b>	215.86	<b>726,107</b>	288.99	<b>727,107</b>	373.57
Inspection Pipe 500mm.	<b>724,120</b>	199.12	<b>725,120</b>	239.65	<b>726,120</b>	329.52	<b>727,120</b>	396.48
Inspection Pyro-Pipe	<b>724,350</b>	287.23	<b>725,350</b>	368.28	<b>726,350</b>	438.77	<b>727,350</b>	504.85
Damper 250mm.	<b>724,134</b>	141.85	<b>725,134</b>	150.66	<b>726,134</b>	200.00	<b>727,134</b>	222.91
Silencer 1000mm.	<b>724,133</b>	207.05	<b>725,133</b>	250.22				
15° Elbow	<b>724,015</b>	115.42	<b>725,015</b>	142.73	<b>726,015</b>	155.07	<b>727,015</b>	225.55
30° Elbow	<b>724,030</b>	115.42	<b>725,030</b>	142.73	<b>726,030</b>	178.85	<b>727,030</b>	232.60
45° Elbow	<b>724,045</b>	117.18	<b>725,045</b>	144.49	<b>726,045</b>	201.76	<b>727,045</b>	260.79
90° Elbow	<b>724,090</b>	199.12	<b>725,090</b>	244.93				
90° Tee	<b>724,109</b>	231.72	<b>725,109</b>	302.20	<b>726,109</b>	363.00	<b>727,109</b>	424.67
135° Tee	<b>724,110</b>	368.28	<b>725,110</b>	437.89	<b>726,110</b>	507.49	<b>727,110</b>	666.96
Locking Band	<b>122,114</b>	13.22	<b>123,114</b>	15.86	<b>124,114</b>	20.88	<b>239,114</b>	21.15
Adjustable Wall Bracket	<b>122,115</b>	28.37	<b>123,115</b>	30.13	<b>124,115</b>	100.44	<b>125,115</b>	114.54
Level Bracket	<b>122,118</b>	55.68	<b>123,118</b>	59.30	<b>124,118</b>	65.02	<b>125,118</b>	70.48
Guy Wire Bracket	<b>122,117</b>	16.12	<b>123,117</b>	18.68	<b>124,117</b>	19.65	<b>125,117</b>	20.35
Descend Bracket	<b>122,181</b>	26.61	<b>123,181</b>	30.84	<b>124,181</b>	34.98	<b>125,181</b>	36.92
Adjustable Wall Support	<b>122,121</b>	112.78	<b>123,121</b>	142.73	<b>124,121</b>	168.28	<b>125,121</b>	211.45
Floor Support	<b>122,124</b>	154.19	<b>123,124</b>	172.69	<b>726,119</b>	167.40		
Base Support with Drain	<b>724,119</b>	130.40	<b>725,119</b>	149.78			<b>727,119</b>	183.26
Roof Support	<b>122,136</b>	45.11	<b>123,136</b>	47.49				0.00
Level Support	<b>122,137</b>	53.74	<b>123,137</b>	57.45	<b>124,137</b>	74.89	<b>125,137</b>	94.27
Conical Terminal	<b>724,111</b>	59.38	<b>725,111</b>	89.87	<b>726,111</b>	111.89	<b>727,111</b>	124.23
Rain Cap	<b>122,112</b>	61.06	<b>123,112</b>	74.89	<b>726,112</b>	108.37	<b>727,112</b>	121.59
Anti-Rain Top Terminal	<b>122,123</b>	66.96	<b>123,123</b>	103.08				
Anti-Flying Top Terminal	<b>122,127</b>	74.01	<b>123,127</b>	105.73	<b>124,127</b>	132.16	<b>125,127</b>	148.90
Anti-Wind Top Terminal	<b>122,125</b>	86.34	<b>123,125</b>	109.25	<b>124,125</b>	135.68	<b>125,125</b>	155.07
Dynamic Raincap	<b>121,131</b>	80.18	<b>122,131</b>	103.96				
Boiler Adaptor (*)	<b>122,150</b>	33.66 (∅ 200)	<b>123,150</b>	36.30 (∅ 250)	<b>726,150</b>	55.77 (∅ 350)	<b>727,150</b>	60.35 (∅ 400)
Boiler Adaptor			<b>725,151</b>	39.74 (∅ 300)				
Boiler Adaptor	<b>122,152</b>	33.66 (∅ 300)						
Single-Double Adaptor	<b>724,148</b>	38.50	<b>725,148</b>	41.50	<b>726,148</b>	62.73	<b>727,148</b>	66.96
Double-Single Adaptor	<b>724,149</b>	38.50	<b>725,149</b>	41.50	<b>726,149</b>	62.73	<b>727,149</b>	66.96
Adaptor GC to MD	<b>531,170</b>	86.34	<b>532,170</b>	106.61	<b>533,170</b>	148.02	<b>534,170</b>	170.04
Adaptor MD to GC	<b>531,171</b>	86.34	<b>532,171</b>	106.61	<b>533,171</b>	148.02	<b>534,171</b>	170.04
Increaser (*)	<b>724,160</b>	132.16 (∅ 300)	<b>725,160</b>	148.90 (∅ 350)	<b>726,160</b>	227.31 (∅ 400)	<b>727,160</b>	212.34 (∅ 450)
Increaser	<b>724,161</b>	141.85 (∅ 350)	<b>725,161</b>	172.69 (∅ 400)				
Increaser								
Teecap	<b>122,113</b>	32.60	<b>123,113</b>	38.15	<b>124,113</b>	47.84	<b>125,113</b>	54.98
Teecap with Drain	<b>122,145</b>	34.01	<b>123,145</b>	39.03	<b>124,145</b>	50.57	<b>125,145</b>	57.62
Firestop Plate	<b>122,140</b>	23.96	<b>123,140</b>	26.52	<b>124,140</b>	37.18	<b>125,140</b>	44.32
Support Plate & Clamp	<b>122,182</b>	47.84	<b>123,182</b>	53.48				
Base Support Plate	<b>724,183</b>	57.27	<b>725,183</b>	70.48				
0° - 10° Flashing	<b>122,129</b>	72.25	<b>123,129</b>	78.41	<b>124,129</b>	126.87	<b>125,129</b>	144.49
5° - 35° Flashing	<b>122,130</b>	72.25	<b>123,130</b>	78.41	<b>124,130</b>	126.87	<b>125,130</b>	144.49
30° - 45° Flashing	<b>122,147</b>	72.25	<b>123,147</b>	78.41	<b>124,147</b>	126.87	<b>125,147</b>	144.49
Storm Collar	<b>122,132</b>	23.96	<b>123,132</b>	26.52	<b>124,132</b>	37.18	<b>125,132</b>	44.32

(\* ) These sizes made to order



# Negarra GC Plus

**Twin-Wall Insulated Flue (AISI 316 inner/304 outer)**  
For use with Gas/Oil Domestic and Commercial Condensing Appliances  
Low Thermal Inertia, No Internal Ridging, Continuous Insulation

Description	80mm Diameter		100mm Diameter		125mm Diameter		150mm Diameter	
	Code	£	Code	£	Code	£	Code	£
Pipe 250mm. ☐	<b>625,104</b>	54.07	<b>626,104</b>	60.11	<b>627,104</b>	67.37	<b>628,104</b>	72.62
Pipe 500mm. ☐	<b>625,105</b>	57.22	<b>626,105</b>	63.52	<b>627,105</b>	70.86	<b>628,105</b>	76.99
Pipe 1000mm. ☐	<b>625,106</b>	79.61	<b>626,106</b>	88.37	<b>627,106</b>	98.87	<b>628,106</b>	111.12
Adj. Pipe 250-450mm. ☐	<b>625,108</b>	98.87	<b>626,108</b>	110.23	<b>627,108</b>	122.48	<b>628,108</b>	135.60
Adj. Pipe 500-950mm. ☐	<b>625,107</b>	119.86	<b>626,107</b>	133.86	<b>627,107</b>	148.73	<b>628,107</b>	163.61
Insptn. Pipe 500mm. ☐	<b>625,120</b>	95.36	<b>626,120</b>	106.74	<b>627,120</b>	118.11	<b>628,120</b>	133.86
Inspection Pyro-Pipe ☐	<b>625,350</b>	244.10	<b>626,350</b>	267.72	<b>627,350</b>	292.21	<b>628,350</b>	316.71
Damper 250mm. ☐	<b>625,134</b>	118.98	<b>626,134</b>	120.73	<b>627,134</b>	123.37	<b>628,134</b>	126.86
Silencer 1000mm. ☐	<b>625,133</b>	99.74	<b>626,133</b>	111.12	<b>627,133</b>	123.37	<b>628,133</b>	139.11
30° Elbow ☐	<b>625,030</b>	61.25	<b>626,030</b>	70.86	<b>627,030</b>	78.74	<b>628,030</b>	80.49
45° Elbow ☐	<b>625,045</b>	64.74	<b>626,045</b>	75.24	<b>627,045</b>	83.11	<b>628,045</b>	85.74
85° Elbow ☐	<b>625,090w</b>	90.12	<b>626,090w</b>	104.99	<b>627,090w</b>	122.48	<b>628,090w</b>	122.48
90° Tee ☐	<b>625,109</b>	130.36	<b>626,109</b>	145.23	<b>627,109</b>	160.98	<b>628,109</b>	179.36
95° Tee ☐	<b>625,109w</b>	167.98	<b>626,109w</b>	209.97	<b>627,109w</b>	183.73	<b>628,109w</b>	218.73
135° Tee ☐	<b>637,110</b>	170.37	<b>638,110</b>	195.30	<b>639,110</b>	207.31	<b>640,110</b>	235.63
Locking Band	<b>231,114</b>	5.86	<b>232,114</b>	6.91	<b>233,114</b>	7.44	<b>234,114</b>	8.75
Adjustable Wall Bracket	<b>231,115</b>	5.60	<b>232,115</b>	5.95	<b>118,115</b>	18.81	<b>119,115</b>	20.56
Level Bracket	<b>231,118</b>	36.40	<b>232,118</b>	37.62	<b>118,118</b>	37.18	<b>119,118</b>	40.33
Guy Wire Bracket	<b>231,117</b>	6.65	<b>232,117</b>	7.44	<b>118,117</b>	12.95	<b>119,117</b>	13.38
Descend Bracket	<b>231,181</b>	15.48	<b>232,181</b>	16.62	<b>118,181</b>	18.37	<b>119,181</b>	21.08
Adjustable Wall Support	<b>231,121</b>	54.85	<b>232,121</b>	63.35	<b>118,121</b>	62.81	<b>119,121</b>	72.62
Base Support & Drain ☐	<b>625,119</b>	76.12	<b>626,119</b>	79.61	<b>627,119</b>	84.87	<b>628,119</b>	94.49
Conical Terminal ☐	<b>625,111</b>	41.82	<b>626,111</b>	44.00	<b>627,111</b>	48.91	<b>628,111</b>	57.05
Anti-Wind Top Terminal ☐		0.00	<b>526,125</b>	47.59	<b>527,125</b>	67.37	<b>528,125</b>	77.87
Static Terminal ☐	<b>525,131</b>	44.18	<b>526,131</b>	44.18	<b>527,131</b>	46.64	<b>528,131</b>	50.30
Horizontal Terminal ☐	<b>625,122</b>	45.41	<b>626,122</b>	46.28	<b>627,122</b>	47.42	<b>628,122</b>	53.89
Boiler Adaptor ☐	<b>625,150</b>	36.84	<b>626,150</b>	37.53	<b>627,150</b>	38.41	<b>628,150</b>	43.74
Flange Adaptor ☐	<b>625,151</b>	42.61	<b>626,151</b>	43.40	<b>627,151</b>	44.54	<b>628,151</b>	50.65
Ad.MD-DC-25 Ø125GC					<b>527,170</b>	53.02	<b>528,170</b>	58.18
Ad.MD-DC-25 Ø125GC					<b>527,171</b>	53.02	<b>528,171</b>	58.18
Boiler Adap GC-25 to IS	<b>525,152</b>	34.12	<b>526,152</b>	34.74	<b>527,152</b>	35.61	<b>528,152</b>	40.51
Boiler Adap IS to GC-25	<b>525,153</b>	34.12	<b>526,153</b>	34.74	<b>527,153</b>	35.61	<b>528,153</b>	40.51
Increaser ☐	<b>625,160</b>	81.36 (Ø 100)	<b>626,160</b>	83.11 (Ø 125)	<b>627,160</b>	84.87 (Ø 150)	<b>628,160</b>	96.23 (Ø 175)
Teecap with Drain ☐	<b>525,145</b>	66.49	<b>526,145</b>	74.37	<b>527,145</b>	82.24	<b>528,145</b>	89.24
Teecap	<b>230,113</b>	8.80	<b>231,113</b>	8.97	<b>232,113</b>	10.64	<b>233,113</b>	12.14
0° - 10° Flashing	<b>231,129</b>	47.94	<b>232,129</b>	50.13	<b>118,129</b>	50.22	<b>119,129</b>	58.09
5° - 35° Flashing	<b>231,130</b>	47.94	<b>232,130</b>	50.13	<b>118,130</b>	50.22	<b>119,130</b>	58.09
30° - 45° Flashing	<b>231,147</b>	47.94	<b>232,147</b>	50.13	<b>118,147</b>	50.22	<b>119,147</b>	58.09
Storm Collar	<b>231,132</b>	13.83	<b>232,132</b>	14.00	<b>118,132</b>	18.72	<b>119,132</b>	20.21

(\* ) These sizes made to order



# Negarra GC Plus

**Twin-Wall Insulated Flue (AISI 316 inner/304 outer)**  
**For use with Gas/Oil Domestic and Commercial Condensing Appliances**  
**Low Thermal Inertia, No Internal Ridging, Continuous Insulation**

Description	175mm Diameter		200mm Diameter		250mm Diameter		300mm Diameter	
	Code	£	Code	£	Code	£	Code	£
Pipe 250mm. □	<b>629,104</b>	74.37	<b>630,104</b>	76.99	<b>631,104</b>	97.98	<b>632,104</b>	108.48
Pipe 500mm. □	<b>629,105</b>	80.49	<b>630,105</b>	88.37	<b>631,105</b>	104.99	<b>632,105</b>	121.61
Pipe 1000mm. □	<b>629,106</b>	129.49	<b>630,106</b>	144.36	<b>631,106</b>	178.48	<b>632,106</b>	215.23
Adj. Pipe 250-450mm. □	<b>629,108</b>	143.48	<b>630,108</b>	154.86	<b>631,108</b>	179.36	<b>632,108</b>	198.60
Adj. Pipe 500-950mm. □	<b>629,107</b>	172.35	<b>630,107</b>	195.98	<b>631,107</b>	215.23	<b>632,107</b>	238.84
Insptn. Pipe 500mm. □	<b>629,120</b>	155.73	<b>630,120</b>	173.23	<b>631,120</b>	214.36	<b>632,120</b>	258.97
Inspection Pyro-Pipe □	<b>629,350</b>	340.33	<b>630,350</b>	364.83	<b>631,350</b>	386.71	<b>632,350</b>	447.94
Damper 250mm. □	<b>629,134</b>	133.86	<b>630,134</b>	137.35	<b>631,134</b>	144.36	<b>632,134</b>	153.98
Silencer 1000mm. □	<b>629,133</b>	161.85	<b>630,133</b>	180.23	<b>631,133</b>	223.97	<b>632,133</b>	269.47
30° Elbow □	<b>629,030</b>	89.24	<b>630,030</b>	91.86	<b>631,030</b>	109.36	<b>632,030</b>	132.98
45° Elbow □	<b>629,045</b>	94.49	<b>630,045</b>	96.23	<b>631,045</b>	117.24	<b>632,045</b>	153.11
85° Elbow □	<b>629,090w</b>	131.23	<b>630,090w</b>	166.23	<b>631,090w</b>	201.22	<b>632,090w</b>	240.59
90° Tee □	<b>629,109</b>	194.23	<b>630,109</b>	222.22	<b>631,109</b>	255.47	<b>632,109</b>	321.09
95° Tee □	<b>629,109w</b>	249.34	<b>630,109w</b>	262.47	<b>631,109w</b>	314.96	<b>632,109w</b>	411.21
135° Tee □	<b>641,110</b>	289.81	<b>642,110</b>	308.83	<b>643,110</b>	345.05	<b>644,110</b>	477.60
90° Reducing Tee □					<b>XXX,109e</b>	184.70	<b>XXX,109E</b>	228.68
Locking Band	<b>235,114</b>	9.63	<b>236,114</b>	10.06	<b>237,114</b>	10.41	<b>238,114</b>	18.55
Adjustable Wall Bracket	<b>120,115</b>	22.83	<b>121,115</b>	24.67	<b>122,115</b>	67.37	<b>123,115</b>	75.24
Level Bracket	<b>120,118</b>	44.80	<b>121,118</b>	50.48	<b>122,118</b>	55.30	<b>123,118</b>	58.88
Guy Wire Bracket	<b>120,117</b>	13.65	<b>121,117</b>	14.52	<b>122,117</b>	16.01	<b>123,117</b>	18.55
Descend Bracket	<b>120,181</b>	22.75	<b>121,181</b>	24.50	<b>122,181</b>	26.42	<b>123,181</b>	30.62
Adjustable Wall Suport	<b>120,121</b>	81.36	<b>121,121</b>	90.99	<b>122,121</b>	111.99	<b>123,121</b>	141.73
Base Support & Drain □	<b>629,119</b>	101.49	<b>630,119</b>	110.23	<b>631,119</b>	125.11	<b>632,119</b>	144.36
Conical Terminal □	<b>629,111</b>	61.68	<b>630,111</b>	69.99	<b>631,111</b>	77.87	<b>632,111</b>	117.24
Anti-Wind Top Terminal □	<b>529,125</b>	77.87	<b>530,125</b>	84.87	<b>531,125</b>	97.12	<b>532,125</b>	121.61
Static Terminal □	<b>529,131</b>	55.65	<b>530,131</b>	70.86	<b>531,131</b>	82.24	<b>532,131</b>	104.11
Horizontal Terminal □	<b>629,122</b>	59.67	<b>630,122</b>	70.86	<b>631,122</b>	88.37	<b>632,122</b>	111.12
Boiler Adaptor □	<b>629,150</b>	48.38	<b>630,150</b>	57.66	<b>631,150</b>	71.75	<b>632,150</b>	90.12
Flange Adaptor □	<b>629,151</b>	55.99	<b>630,151</b>	67.37	<b>631,151</b>	83.11	<b>632,151</b>	104.11
Ad.MD-DC-25 Ø125GC	<b>529,170</b>	68.24	<b>530,170</b>	82.24	<b>531,170</b>	91.86	<b>532,170</b>	112.87
Ad.MD-DC-25 Ø125GC	<b>529,171</b>	68.24	<b>530,171</b>	82.24	<b>531,171</b>	91.86	<b>532,170</b>	112.87
Adaptor GC-25 to IS	<b>529,152</b>	44.80	<b>530,152</b>	53.37	<b>531,152</b>	66.49	<b>532,152</b>	66.49
Adaptor IS to GC-25	<b>529,153</b>	44.80	<b>530,153</b>	53.37	<b>531,153</b>	66.49	<b>532,153</b>	66.49
Increaser □	<b>629,160</b>	118.11 (Ø 200)	<b>630,160</b>	132.98 (Ø 250)	<b>631,160</b>	173.23 (Ø 300)	<b>632,160</b>	204.73 (Ø 350)
Teecap with Drain □	<b>529,145</b>	90.99	<b>530,145</b>	93.61	<b>531,145</b>	120.73	<b>532,145</b>	132.98
Teecap	<b>234,113</b>	13.54	<b>235,113</b>	16.71	<b>236,113</b>	18.29	<b>237,113</b>	19.70
0° - 10° Flashing	<b>120,129</b>	64.30	<b>121,129</b>	69.11	<b>122,129</b>	71.75	<b>123,129</b>	77.87
5° - 35° Flashing	<b>120,130</b>	64.30	<b>121,130</b>	69.11	<b>122,130</b>	71.75	<b>123,130</b>	77.87
30° - 45° Flashing	<b>120,147</b>	64.30	<b>121,147</b>	69.11	<b>122,147</b>	71.75	<b>123,147</b>	77.87
Storm Collar	<b>120,132</b>	20.47	<b>121,132</b>	21.96	<b>122,132</b>	23.79	<b>123,132</b>	26.34

(\* ) These sizes made to order



# Negarra GC Plus

**Twin-Wall Insulated Flue (AISI 316 inner/304 outer)**  
For use with Gas/Oil Domestic and Commercial Condensing Appliances  
Low Thermal Inertia, No Internal Ridging, Continuous Insulation

Description	350mm. diameter		400mm. Diameter		450mm. Diameter		500mm. diameter	
	code	£	code	£	code	£	code	£
Pipe 250mm. □	<b>633,104</b>	119.86	<b>634,104</b>	172.36	<b>635,104</b>	192.48	<b>636,104</b>	203.85
Pipe 500mm. □	<b>633,105</b>	158.35	<b>634,105</b>	215.23	<b>635,105</b>	216.10	<b>636,105</b>	230.97
Pipe 1000mm. □	<b>633,106</b>	295.72	<b>634,106</b>	356.08	<b>635,106</b>	363.08	<b>636,106</b>	377.08
Adjust. Pipe 250-450mm. □	<b>633,108</b>	264.22	<b>634,108</b>	339.46	<b>635,108</b>	363.96	<b>636,108</b>	398.08
Adjust. Pipe 500-950mm. □	<b>633,107</b>	319.34	<b>634,107</b>	412.08	<b>635,107</b>	442.70	<b>636,107</b>	482.94
Insptn. Pipe 500mm. □	<b>633,120</b>	355.21	<b>634,120</b>	426.95	<b>635,120</b>	435.70	<b>636,120</b>	452.32
Inspection Pyro-Pipe □	<b>633,350</b>	508.31	<b>634,350</b>	568.68	<b>635,350</b>	629.05	<b>636,350</b>	689.42
Damper 250mm. □	<b>633,134</b>	184.60	<b>634,134</b>	204.73	<b>635,134</b>	215.23	<b>636,134</b>	243.22
Silencer 1000mm. □	<b>633,133</b>	287.84	<b>634,133</b>	307.96	<b>635,133</b>	340.34	<b>636,133</b>	374.46
30° Elbow □	<b>633,030</b>	178.48	<b>634,030</b>	393.70	<b>635,030</b>	409.45	<b>636,030</b>	456.70
45° Elbow □	<b>633,045</b>	200.35	<b>634,045</b>	438.32	<b>635,045</b>	521.44	<b>636,045</b>	644.80
90° Tee □	<b>633,109</b>	614.18	<b>634,109</b>	839.90	<b>635,109</b>	728.79	<b>636,109</b>	803.16
135° Tee □	<b>645,110</b>	611.28	<b>646,110</b>	679.18	<b>647,110</b>	736.36	<b>648,110</b>	863.71
90° Reducing Tee □	<b>XXX,109E</b>	617.44	<b>XXX,109E</b>	844.36	<b>XXX,109E</b>		<b>XXX,109E</b>	807.42
Locking Band	<b>238,114</b>	20.73	<b>534,114</b>	20.39	<b>535,114</b>	20.56	<b>536,114</b>	21.61
Adjustable Wall Bracket	<b>124,115</b>	99.74	<b>125,115</b>	113.74	<b>240,115</b>	137.36	<b>242,115</b>	165.36
Level Bracket	<b>124,118</b>	64.57	<b>125,118</b>	69.99	<b>240,118</b>	82.24	<b>242,118</b>	107.61
Guy Wire Bracket	<b>124,117</b>	19.51	<b>125,117</b>	20.21	<b>240,117</b>	25.72	<b>242,117</b>	29.31
Descend Bracket	<b>124,181</b>	34.74	<b>125,181</b>	36.66	<b>240,181</b>	45.93		
Adjustable Wall Suport	<b>124,121</b>	167.11	<b>125,121</b>	209.98	<b>240,121</b>	252.85	<b>242,121</b>	228.35
Base Support & Drain □	<b>633,119</b>	153.98	<b>634,119</b>	174.98	<b>635,119</b>	205.60	<b>636,119</b>	248.47
Conical Terminal □	<b>633,111</b>	119.86	<b>634,111</b>	133.86	<b>635,111</b>	139.98	<b>636,111</b>	148.73
Anti-Wind Top Terminal □	<b>533,125</b>	151.36	<b>534,125</b>	173.23	<b>535,125</b>	177.60	<b>536,125</b>	202.98
Horizontal Terminal □	<b>633,122</b>	95.36	<b>634,122</b>	109.36	<b>635,122</b>	114.61	<b>636,122</b>	125.11
Boiler AdapØ350GC25Plus	<b>633,150</b>	72.62	<b>634,150</b>	77.87	<b>635,150</b>	87.49	<b>636,150</b>	95.36
Flange Adaptor □	<b>633,151</b>	84.00	<b>634,151</b>	96.24	<b>635,151</b>	101.49	<b>636,151</b>	110.24
Adapt. from GC-25 to MD	<b>633,170</b>	157.48	<b>634,170</b>	181.10				
Adapt. from MD to GC-25	<b>633,171</b>	157.48	<b>634,171</b>	181.10				
Adaptor GC-25 to IS	<b>533,152</b>	67.37	<b>534,152</b>	76.99	<b>535,152</b>	80.49	<b>536,152</b>	88.36
Adaptor IS to GC-25	<b>533,153</b>	67.37	<b>534,153</b>	76.99	<b>535,153</b>	80.49	<b>536,153</b>	88.36
Increaser □	<b>633,160</b>	221.35 (Ø 400)	<b>634,160</b>	252.85 (Ø 450)	<b>635,160</b>	269.47 (Ø 500)	<b>636,160</b>	308.84 (Ø 550)
Teecap with Drain □	<b>533,145</b>	146.98	<b>534,145</b>	211.73	<b>535,145</b>	235.35	<b>536,145</b>	249.35
Teecap	<b>238,113</b>	22.69	<b>239,113</b>	24.80	<b>240,113</b>	33.86	<b>242,113</b>	40.37
0° - 10° Flashing	<b>124,129</b>	125.99	<b>125,129</b>	143.48	<b>240,129</b>	170.61	<b>242,129</b>	195.98
5° - 35° Flashing	<b>124,130</b>	125.99	<b>125,130</b>	143.48	<b>240,130</b>	170.61	<b>242,130</b>	195.98
30° - 45° Flashing	<b>124,147</b>	125.99	<b>125,147</b>	143.48	<b>240,147</b>	170.61	<b>242,147</b>	195.98
Storm Collar	<b>124,132</b>	36.92	<b>125,132</b>	44.01	<b>240,132</b>	51.53	<b>242,132</b>	56.08

(\* ) These sizes made to order



# Negarra GC Plus

**Twin-Wall Insulated Flue (AISI 316 inner/304 outer)**  
**For use with Gas/Oil Domestic and Commercial Condensing Appliances**  
**Low Thermal Inertia, No Internal Ridging, Continuous Insulation**

Description	550mm. Diameter		600mm. Diameter		650mm. Diameter	
	code	£	code	£	code	£
Pipe 250mm. ☐	<b>637,104</b>	218.72	<b>638,104</b>	239.72	<b>639,104</b>	263.34
Pipe 500mm. ☐	<b>637,105</b>	246.72	<b>638,105</b>	265.97	<b>639,105</b>	293.09
Pipe 1000mm. ☐	<b>637,106</b>	403.33	<b>638,106</b>	420.83	<b>639,106</b>	463.70
Adjust. Pipe 250-450mm. ☐	<b>637,108</b>	426.08	<b>638,108</b>	457.57	<b>639,108</b>	503.94
Adjust. Pipe 500-950mm. ☐	<b>637,107</b>	517.07	<b>638,107</b>	558.19	<b>639,107</b>	615.05
Insptn. Pipe 500mm. ☐	<b>637,120</b>	483.82	<b>638,120</b>	513.57	<b>639,120</b>	566.06
Inspection Pyro-Pipe ☐	<b>637,350</b>	693.80	<b>638,350</b>	809.28	<b>639,350</b>	870.53
Damper 250mm. ☐	<b>637,134</b>	277.34	<b>638,134</b>	287.84	<b>639,134</b>	306.21
Silencer 1000mm. ☐	<b>637,133</b>	377.96	<b>638,133</b>	454.95	<b>639,133</b>	501.32
30° Elbow ☐	<b>637,030</b>	570.43	<b>638,030</b>	634.30	<b>639,030</b>	676.30
45° Elbow ☐	<b>637,045</b>	642.18	<b>638,045</b>	721.79	<b>639,045</b>	768.16
90° Tee ☐	<b>637,109</b>	896.77	<b>638,109</b>	965.89	<b>639,109</b>	1,049.88
135° Tee ☐	<b>649,110</b>	960.46	<b>650,110</b>	1,143.41	<b>651,110</b>	1,407.27
90° Reducing Tee ☐	<b>XXX,109E</b>	901.53	<b>XXX,109E</b>	971.02	<b>XXX,109E</b>	1,055.45
Locking Band	<b>537,114</b>	23.53	<b>538,114</b>	24.76	<b>539,114</b>	26.95
Adjustable Wall Bracket	<b>243,115</b>	177.60	<b>244,115</b>	208.23	<b>245,115</b>	287.84
Level Bracket	<b>243,118</b>	122.49	<b>244,118</b>	139.11	<b>245,118</b>	159.23
Guy Wire Bracket	<b>243,117</b>	33.42	<b>244,117</b>	37.53	<b>245,117</b>	43.05
Adjustable Wall Support	<b>537,121</b>	244.10	<b>538,121</b>	270.34	<b>539,121</b>	372.71
Base Support & Drain ☐	<b>637,119</b>	265.97	<b>638,119</b>	314.09	<b>639,119</b>	432.20
Conical Terminal ☐	<b>637,111</b>	159.23	<b>638,111</b>	195.10	<b>639,111</b>	215.23
Horizontal Terminal ☐	<b>637,122</b>	136.48	<b>638,122</b>	153.11	<b>639,122</b>	162.73
Boiler AdapØ350GC25Plus	<b>637,150</b>	104.11	<b>638,150</b>	116.36	<b>639,150</b>	123.36
Flange Adaptor ☐	<b>637,151</b>	119.86	<b>638,151</b>	134.73	<b>639,151</b>	142.61
Adaptor GC-25 to IS	<b>537,152</b>	96.24	<b>538,152</b>	107.61	<b>539,152</b>	114.61
Adaptor IS to GC-25	<b>537,153</b>	96.24	<b>538,153</b>	107.61	<b>539,153</b>	114.61
Increaser ☐	<b>637,160</b>	330.71 (Ø 600)	<b>638,160</b>	353.46 (Ø 650)		
Teecap with Drain ☐	<b>537,145</b>	266.84	<b>538,145</b>	292.22	<b>539,145</b>	312.34
Teecap	<b>243,113</b>	44.24	<b>244,113</b>	50.75	<b>245,113</b>	57.35
0° - 10° Flashing	<b>243,129</b>	211.73	<b>244,129</b>	233.60	<b>245,129</b>	242.35
5° - 35° Flashing	<b>243,130</b>	211.73	<b>244,130</b>	233.60	<b>245,130</b>	242.35
30° - 45° Flashing	<b>243,147</b>	211.73	<b>244,147</b>	233.60	<b>245,147</b>	242.35
Storm Collar	<b>243,132</b>	65.27	<b>244,132</b>	70.87	<b>245,132</b>	79.62

(\* ) These sizes made to order